

Description

Fastener Length: 1-3/16", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1154E14
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-535-1780
Schedule B:	7318.15.6080
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS1154E14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.316 Inches Nominal
Fastener Length:	1.191 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.449 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Internal Drive Style:	Offset Cruciform (torque Set)
End Item Identification:	U-2
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.050 Inches Minimum First Hole And 1.090 Inches Maximum First Hole
Part Name Assigned By Controlling Agency:	Flat 100 Deg Head,close Tolerance, Short Thread,offset Cruciform,160ksi
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1154E14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.