

**Description**

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS1154V11A                          |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-01-328-7907                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |



\* See page 2 for technical characteristics

## P/N NAS1154V11A Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.316 Inches Nominal                                       |
| <b>Fastener Length:</b>                               | 0.989 Inches Minimum And 1.019 Inches Maximum              |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.449 Inches Minimum And 0.507 Inches Maximum              |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum            |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                              |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Grip Length:</b>                                   | 0.678 Inches Minimum And 0.698 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum             |
| <b>Material:</b>                                      | Titanium Alloy Uns R56400 Overall                          |
| <b>Material Document And Classification:</b>          | Ams 4967 Assn Std Single Material Response Overall         |
| <b>Surface Treatment:</b>                             | Aluminum Overall   |
| <b>Surface Treatment Document And Classification:</b> | Nas4006 Assn Std Single Treatment Response Overall         |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1154 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1154V11A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.