



Military-Fasteners.com

P/N NAS1154V4

Description

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 21/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1154V4
Minimum Qty (MOQ):	100
NSN:	5305-00-939-0796
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096660, Screws Noi Silver Plated



* See page 2 for technical characteristics

P/N NAS1154V4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.291 Inches Minimum And 0.341 Inches Maximum
Fastener Length:	0.551 Inches Minimum And 0.581 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.449 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1154 Professional/industrial Association Standard

How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1154V4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.