

P/N NAS1154V5

Description

Length: 41/64", Thread: 1/4-28, Thread Length: 5/16", NAS1154 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1154V5

Minimum Qty (MOQ):

NSN: 5305-00-917-6277

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1154V5 Specifications

| Thread Class: | 3a |
|---------------------------------------|--|
| Thread Direction: | Right-hand |
| Thread Length: | 0.316 Inches Minimum |
| Fastener Length: | 0.613 Inches Minimum And 0.643 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.449 Inches Minimum And 0.507 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.312 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Uns R54520 Overall |
| Material Document And Classification: | Nas 621,6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas1154 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/NAS1154V5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.