

Description

Fastener Length: 1-5/16", Thread: 1/4-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS115515 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-889-6589 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS1155-15 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.375 Inches Nominal |
| Fastener Length: | 1.313 Inches Nominal |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.577 Inches Minimum And 0.635 Inches Maximum |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum |
| Countersink Angle: | 100.0 Degrees Nominal |
| Screw Material: | Steel |
| Screw Surface Treatment: | Cadmium And Chromate Or Zinc And Chromate |
| Thread Series Designator: | Unf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1155-15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.