

# P/N NAS1155-15

## **Description**

Fastener Length: 1-5/16", Thread: 1/4-24, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS115515

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-889-6589

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS1155-15 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	1.313 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.577 Inches Minimum And 0.635 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel
Screw Surface Treatment:	Cadmium And Chromate Or Zinc And Chromate
Thread Series Designator:	Unf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/NAS1155-15">https://military-fasteners.com/screws/machine+screws/NAS1155-15</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.