

Description

Fastener Length: 1-25/64", Thread: 1/4-24, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | NAS1155V16 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-00-488-3878 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N NAS1155V16 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.350 Inches Minimum And 0.400 Inches Maximum |
| Fastener Length: | 1.360 Inches Minimum And 1.390 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.577 Inches Minimum And 0.635 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Internal Drive Style: | Offset Cruciform (torque Set) |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Nas 621,composition 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1155V16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.