

Description

Fastener Length: 53/64", Thread: 1/4-24, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1155V7
Minimum Qty (MOQ):	1 EA
NSN:	5305-00-916-9493
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS1155V7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Minimum
Fastener Length:	0.798 Inches Minimum And 0.828 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.577 Inches Minimum And 0.635 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.438 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas 621 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1155 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1155V7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.