

Description

Fastener Length: 1-21/32", Thread: 3/8-24, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS115620
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-014-5480
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1156-20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.366 Inches Minimum And 0.416 Inches Maximum
Fastener Length:	1.626 Inches Minimum And 1.656 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.704 Inches Minimum And 0.762 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	101.0 Degrees Nominal
Surface Finish:	32.0 Microinches Overall
Material:	Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1156 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1156-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.