

**Description**

Fastener Length: 1-21/32", Thread: 3/8-24, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS115620                                 |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5305-01-014-5480                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1156-20 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.366 Inches Minimum And 0.416 Inches Maximum               |
| <b>Fastener Length:</b>                               | 1.626 Inches Minimum And 1.656 Inches Maximum               |
| <b>Head Style:</b>                                    | Flat Countersunk  |
| <b>Head Diameter:</b>                                 | 0.704 Inches Minimum And 0.762 Inches Maximum               |
| <b>Grip Diameter:</b>                                 | 0.3735 Inches Minimum And 0.3745 Inches Maximum             |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                               |
| <b>Nominal Thread Diameter:</b>                       | 0.375 Inches  |
| <b>Grip Length:</b>                                   | 1.240 Inches Minimum And 1.260 Inches Maximum               |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                               |
| <b>Countersink Angle:</b>                             | 101.0 Degrees Nominal                                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Overall                                    |
| <b>Material:</b>                                      | Steel Comp 4140 Overall                                     |
| <b>Material Document And Classification:</b>          | Mil-s-5626 Mil Spec Single Material Response Overall        |
| <b>Surface Treatment:</b>                             | Cadmium Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas1156 Professional/industrial Association Standard  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1156-20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.