

Description

NAS1160-4-16 Shoulder Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1160416 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-488-2238 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N NAS1160-4-16 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.291 Inches Minimum And 0.308 Inches Maximum |
| Fastener Length: | 1.443 Inches Minimum And 1.483 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| End Item Identification: | S-3a |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 4500 Pounds Per Square Inch |
| Shoulder Shape: | Round Overall |
| Special Features: | Bolt Is Close Tolerance |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Ams 5731 Assn Std 1st Material Response Overall Or Ams 5737 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35, Type Ii Or Viii Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS1160-4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.