

P/N NAS1169-C416L

Description

size: 1/4", dimpled, corrosion resistant steel, NAS1169 series washer

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS1169C416L
Minimum Qty (MOQ):	100
NSN:	5310-01-052-3343
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



^{*} See page 2 for technical characteristics

P/N NAS1169-C416L Specifications

Hole Diameter:	0.252 Inches Minimum And 0.282 Inches Maximum
Outside Diameter:	0.745 Inches Minimum And 0.770 Inches Maximum
Overall Height:	0.125 Inches Nominal
Recess Diameter:	0.507 Inches Minimum And 0.517 Inches Maximum
Material Thickness:	0.014 Inches Minimum And 0.018 Inches Maximum
Recess Angle:	99.0 Degrees Minimum And 103.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	A286 Per Ams5735 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Finishing
Specification/standard Data:	80205-nas1169 Professional/industrial Association Standard

How to Order

Order this finishing washer from our inventory online by visiting https://military-fasteners.com/washers/finishing+washers/NAS1169-C416L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/finishing+washers/NAS1169-C416L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/finishing+washers/NAS1169-C416L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/washers/NAS1169-C416L and selecting the quantity your want then click "add to cart".