

Description

size: 1/4", dimpled, corrosion resistant steel, NAS1169 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1169C416
Minimum Qty (MOQ):	25
NSN:	5310-01-109-2201
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



* See page 2 for technical characteristics

P/N NAS1169C416 Specifications

Hole Diameter:	0.252 Inches Minimum And 0.282 Inches Maximum
Outside Diameter:	0.745 Inches Minimum And 0.770 Inches Maximum
Overall Height:	0.132 Inches Nominal
Recess Diameter:	0.507 Inches Minimum And 0.517 Inches Maximum
Material Thickness:	0.022 Inches Minimum And 0.028 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Recess Angle:	99.0 Degrees Minimum And 103.0 Degrees Maximum
Material Document And Classification:	Ams 5732 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Finishing
Specification/standard Data:	80205-nas1169 Professional/industrial Association Standard

How to Order

Order this finishing washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/NAS1169C416> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.