

Description

corrosion resistant steel - size: #6, dimpled washer 100â°

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1169C6L
Minimum Qty (MOQ):	100
NSN:	5310-01-080-2224
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,

NO IMAGE
AVAILABLE

P/N NAS1169C6L Specifications

Hole Diameter:	0.140 Inches Minimum And 0.170 Inches Maximum
Outside Diameter:	0.470 Inches Minimum And 0.495 Inches Maximum
Overall Height:	0.076 Inches Nominal
Recess Diameter:	0.279 Inches Minimum And 0.289 Inches Maximum
Material Thickness:	0.016 Inches Nominal
Recess Angle:	99.0 Degrees Minimum And 103.0 Degrees Maximum
Material Document And Classification:	Ams5525 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Finishing
Specification/standard Data:	80205-nas1169 Professional/industrial Association Standard

How to Order

Order this finishing washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/NAS1169C6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.