

Description

corrosion resistant steel - size: #6, dimpled washer 100â°

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1169C6L |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-01-080-2224 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



P/N NAS1169C6L Specifications

| | |
|---|--|
| Hole Diameter: | 0.140 Inches Minimum And 0.170 Inches Maximum |
| Outside Diameter: | 0.470 Inches Minimum And 0.495 Inches Maximum |
| Overall Height: | 0.076 Inches Nominal |
| Recess Diameter: | 0.279 Inches Minimum And 0.289 Inches Maximum |
| Material Thickness: | 0.016 Inches Nominal |
| Recess Angle: | 99.0 Degrees Minimum And 103.0 Degrees Maximum |
| Material Document And Classification: | Ams5525 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Style Designator: | Finishing |
| Specification/standard Data: | 80205-nas1169 Professional/industrial Association Standard |

How to Order

Order this finishing washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/NAS1169C6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.