

P/N NAS1169C8L

Description

size: #8, dimpled washer, corrosion resistant steel, NAS1169 series washer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

Alternate Part Numbers

NAS1169-C8L

SKU / Model: NAS1169C8L

Minimum Qty (MOQ): 50

NSN: 5310-01-058-5395

Schedule B: 7318.22.0000

ECCN: EAR99

National Motor Freight: 194160, Washer Or Gaskets, Iron Or Steel,









P/N NAS1169C8L Specifications

Hole Diameter:	0.166 Inches Minimum And 0.196 Inches Maximum
Outside Diameter:	0.557 Inches Minimum And 0.582 Inches Maximum
Overall Height:	0.087 Inches Nominal
Recess Diameter:	0.332 Inches Minimum And 0.342 Inches Maximum
Material Thickness:	0.014 Inches Minimum And 0.018 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Recess Angle:	99.0 Degrees Minimum And 103.0 Degrees Maximum
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Style Designator:	Finishing
Specification/standard Data:	80205-nas1169 Professional/industrial Association Standard

How to Order

Order this finishing washer from our inventory online by visiting https://military-fasteners.com/washers/finishing+washers/NAS1169C8L and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.