

Description

size: 1/4", dimpled, alclad aluminum alloy

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1169DD416L |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5310-00-001-4714 |
| ECCN: | EAR99 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N NAS1169DD416L Specifications

| | |
|---|--|
| Hole Diameter: | 0.252 Inches Minimum And 0.282 Inches Maximum |
| Outside Diameter: | 0.745 Inches Minimum And 0.770 Inches Maximum |
| Overall Height: | 0.125 Inches Nominal |
| Recess Diameter: | 0.507 Inches Minimum And 0.517 Inches Maximum |
| Material Thickness: | 0.016 Inches Nominal |
| Recess Angle: | 99.0 Degrees Minimum And 103.0 Degrees Maximum |
| Special Features: | Dyed Orange Color |
| Material: | Aluminum Alloy 2024 Overall Or Aluminum Alloy 5052 Overall |
| Material Document And Classification: | Qq-a-250/5,t3 Fed Spec 1st Material Response Overall Or Qq-a-250/5,t4 Fed Spec 1st Material Response Overall And Qq-a-250/8,0 Fed Spec 2nd Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Style Designator: | Finishing |
| Specification/standard Data: | 80205-nas1169 Professional/industrial Association Standard |

How to Order

Order this finishing washer from our inventory online by visiting <https://military-fasteners.com/washers/finishing+washers/NAS1169DD416L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.