

P/N NAS1169DD6

Description

alclad aluminum alloy - size: #6, dimpled washer 100âº

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS1169DD6

Minimum Qty (MOQ): 100

NSN: 5310-01-102-3300

National Motor Freight: 194120, Washers / Gaskets / Pckg Dvcs Noi



^{*} See page 2 for technical characteristics

P/N NAS1169DD6 Specifications

Hole Diameter:	0.140 Inches Minimum And 0.170 Inches Maximum
noie Diameter:	0.140 Inches Minimum And 0.170 Inches Maximum
Outside Diameter:	0.470 Inches Minimum And 0.495 Inches Maximum
Overall Height:	0.082 Inches Nominal
Recess Diameter:	0.279 Inches Minimum And 0.289 Inches Maximum
Material Thickness:	0.025 Inches Nominal
Recess Angle:	99.0 Degrees Minimum And 103.0 Degrees Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-250/5,temper T3 Fed Spec Single Material Response Overall Or Qq-a-250/5,temper T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Style Designator:	Finishing
Specification/standard Data:	80205-nas1169 Professional/industrial Association Standard

How to Order

Order this finishing washer from our inventory online by visiting https://military-fasteners.com/washers/finishing+washers/NAS1169DD6 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.