

**Description**

Fastener Length: 3/8", Thread: 6-32, Thread Length: 5/16"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS118906P6L
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-964-0872
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1189-06P6L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.315 Inches Minimum
<b>Fastener Length:</b>	0.375 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.267 Inches Minimum And 0.279 Inches Maximum
<b>Locking Feature:</b>	Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas1189 Professional/industrial Association Standard

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-06P6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.