

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS118906P8
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-165-8025
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1189-06P8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.350 Inches Minimum And 0.443 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.231 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Patch Or Pellet Or Strip
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4140 Or Steel Comp E4340 Or Steel Comp 6150 Or Steel Comp 8735 Or Steel Comp 8740
Screw Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Or Mil-s-5000 Mil Spec 2nd Material Response Or Mil-s-8503 Mil Spec 3rd Material Response Or Mil-s-6098 Mil Spec 4th Material Response Or Mil-s-6049 Mil Spec 5th Material Response
Screw Surface Treatment:	Cadmium And Chromate
Screw Surface Treatment Document And Classification:	Qq-p-416, Ty 2, CI 3 Fed Spec All Treatment Responses
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-06P8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.