

**Description**

Fastener Length: 3/8", Thread: 8-32, Thread Length: 19/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS118908P6
Minimum Qty (MOQ):	25
NSN:	5305-00-954-4421
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS1189-08P6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.272 Inches Minimum And 0.303 Inches Maximum
<b>Fastener Length:</b>	0.344 Inches Minimum And 0.375 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.270 Inches Minimum And 0.332 Inches Maximum
<b>Locking Feature:</b>	Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas1189 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-08P6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.