

Description

Fastener Length: 3/8", Thread: 8-32, Thread Length: 19/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS118908P6L
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-935-3052
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1189-08P6L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.303 Inches Minimum
Fastener Length:	0.375 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.319 Inches Minimum And 0.332 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-08P6L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.