

P/N NAS1189-3P10

Description

Fastener Length: 5/8", Thread: 10-32, Thread Length: 17/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS11893P10

Minimum Qty (MOQ):

NSN: 5305-00-132-1746

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS1189-3P10 Specifications

Thread Direction: Right-hand Thread Length: 0.452 Inches Minimum And 0.545 Inches Maximum Fastener Length: 0.594 Inches Minimum And 0.625 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.322 Inches Minimum And 0.385 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Sidewinder Missille; aidearm Air-to-ground Missille; captor Mine(s) Countermeasures; helio, Elect Countermeasures; helicopter, Iroquois Uh-1; aim Sidewinder Missille; aidearm Air-to-ground Missille; captor Mine(s) Countermeasures; helio, Elect Countermeasures; helicopter, Iroquois Uh-1; aim Sidewinder Missille; aidearm Air-to-ground Missille; captor Mine(s) Countermeasures; helio, Elect Countermeasures; helicopter, Iroquois Uh-1; aim Sidewinder Missille; aidearm Air-to-ground Missille; captor Mine(s) Countermeasures; helio, Elect Countermeasures; helicopter, Iroquois Uh-1; aim Sidewinder Missille; aidearm Air-to-ground Missille; captor Mine(s) Countermeasures; helio, Elect Countermeasures		
Thread Length: 0.452 Inches Minimum And 0.545 Inches Maximum Fastener Length: 0.594 Inches Minimum And 0.625 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.322 Inches Minimum And 0.385 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Xisidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;hellicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 10.1.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4037 Overall Material Document And Classification: Xieles Comp E4340 Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-5039 Mil Spec 3rd Material Response Overall Or Mil-s-5049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Thread Class:	3a
Head Style: Flat Countersunk Head Style: Plat Countersunk Head Diameter: 0.322 Inches Minimum And 0.385 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Xisidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches 10.190 Inches 10.190 Inc	Thread Direction:	Right-hand
Head Style: Flat Countersunk Head Diameter: 0.322 Inches Minimum And 0.385 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Sidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5026 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8030 Alss Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Ath Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec Ath Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6098 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec	Thread Length:	0.452 Inches Minimum And 0.545 Inches Maximum
Head Diameter: 0.322 Inches Minimum And 0.385 Inches Maximum Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Sidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Cadmium Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Document And Classification: Q-q-9-16,ty 2,cl 3 Fed Spec All Treatment Responses Overall Ocument And Classification: Cadmium Overall And Chromate Overall	Fastener Length:	0.594 Inches Minimum And 0.625 Inches Maximum
Locking Feature: Pellet Threads Or Strip Threads Internal Drive Style: Cross Recess Type 1 End Item Identification: Xisidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-6026 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Style:	Flat Countersunk
Internal Drive Style: Cross Recess Type 1 End Item Identification: Sidewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 36.0000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Mil-5-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Stufface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Scalewinder Missile;sidearm Air-to-ground Missile;captor Mine(s) Countermeasures;helo, Elect Countermeasures;helicopter, Iroquois Uh-1;aim Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 O.190 Inches 32	Locking Feature:	Pellet Threads Or Strip Threads
Sidewinder Missile;aircraft, Hercules C-130;chaparral/vulcan Ads;helicopter, Iroquois Hh/uh-1 Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Mill-s-5626 Mil Spec 1st Material Response Overall Or Mill-s-5000 Mil Spec 2nd Material Response Overall Or Mill-s-8503 Mil Spec 3rd Material Response Overall Or Mill-s-6098 Mill Spec 4th Material Response Overall Or Mill-s-6049 Mill Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification: Side Middle Spec All Treatment Responses Overall Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6009 Mil Spec 2nd Material Response Overall Or Mil-s-6030 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Ocument And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall	End Item Identification:	
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6039 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Nominal Thread Diameter:	0.190 Inches
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Thread Quantity Per Inch:	32
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Document And Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: 32.0 Microinches Threads Material: Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Steel Comp 4140 Overall Or Steel Comp E4340 Overall Or Steel Comp 6150 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Mil-s-6049 Mil Sp	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Material Document And Classification: Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-8503 Mil Spec 3rd Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Oq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 6th Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Ocument And Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Material:	
Surface Treatment Document And Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6049 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall Classification:	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
	Thread Series Designator:	Unjf

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS1189-3P10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.