

**Description**

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS11896T12L                              |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-00-921-0007                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1189-6T12L Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 0.585 Inches Minimum  |
| <b>Fastener Length:</b>             | 0.750 Inches Nominal  |
| <b>Head Style:</b>                  | Flat Countersunk  |
| <b>Head Diameter:</b>               | 0.742 Inches Minimum And 0.762 Inches Maximum                       |
| <b>Locking Feature:</b>             | Strip Threads   |
| <b>Internal Drive Style:</b>        | Offset Cruciform (torque Set)                                       |
| <b>Nominal Thread Diameter:</b>     | 0.375 Inches  |
| <b>Thread Quantity Per Inch:</b>    | 24  |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>             | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Countersink Angle:</b>           | 99.0 Degrees Minimum And 101.0 Degrees Maximum                      |
| <b>Material:</b>                    | Steel Overall   |
| <b>Surface Treatment:</b>           | Cadmium Overall And Chromate Overall                                |
| <b>Thread Series Designator:</b>    | Unf   |
| <b>Specification/standard Data:</b> | 80205-nas1189 Professional/industrial Association Standard          |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-6T12L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.