



Military-Fasteners.com

P/N NAS1189-6T12L

Description

Fastener Length: 3/4", Thread: 3/8-24, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS11896T12L
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-921-0007
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189-6T12L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.585 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.742 Inches Minimum And 0.762 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS1189-6T12L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.