

## P/N NAS1189E04P4

## **Description**

Fastener Length: 1/4", Thread: 4-40, Thread Length: 3/16",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1189E04P4

Minimum Qty (MOQ): 50

NSN: 5305-01-042-3747

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1189E04P4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.192 Inches Nominal
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.213 Inches Minimum And 0.225 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	125.0 Microinches Top Of Head
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

## **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P4">https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.