



★ FASTENERS

Military-Fasteners.com

P/N NAS1189E04P4

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 3/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E04P4
Minimum Qty (MOQ):	50
NSN:	5305-01-042-3747
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189E04P4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.192 Inches Nominal
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.213 Inches Minimum And 0.225 Inches Maximum
Locking Feature:	Patch Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	125.0 Microinches Top Of Head
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/Industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.