

Description

Fastener Length: 1/4", Thread: 4-40, Thread Length: 3/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS1189E04P4LK |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-01-059-7439 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1189E04P4LK Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.124 Inches Minimum And 0.200 Inches Maximum |
| Fastener Length: | 0.219 Inches Minimum And 0.250 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.177 Inches Minimum And 0.225 Inches Maximum |
| Locking Feature: | Pellet Threads Or Strip Threads |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.112 Inches |
| Thread Quantity Per Inch: | 40 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams 5737 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjc |
| Specification/standard Data: | 80205-nas1189 Professional/Industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P4LK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.