

# **P/N NAS1189E04P7B**

### **Description**

Fastener Length: 7/16", Thread: 4-40

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1189E04P7B
Minimum Qty (MOQ):	5
NSN:	5305-01-432-9163
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1189E04P7B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.438 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.213 Inches Minimum And 0.225 Inches Maximum
Locking Feature:	Patch
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Locking Feature Material:	Plastic Polyamide
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unjc

### **How to Order**

Order this close tolerance screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B">https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B">https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B">https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P7B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/nasengar/">https://military-fasteners.com/screws/nasengar/</a> and selecting the property of the propert