

Description

Fastener Length: 1/2", Thread: 4-40, Thread Length: 29/64

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1189E04P8B
Minimum Qty (MOQ):	5
NSN:	5305-01-278-9631
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	156600, Plastic / Rubber Article Viz:

NO IMAGE
AVAILABLE

P/N NAS1189E04P8B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.374 Inches Minimum And 0.455 Inches Maximum
Fastener Length:	0.469 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.177 Inches Minimum And 0.225 Inches Maximum
Locking Feature:	Patch Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams5737 Assn Std Single Material Response Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS1189E04P8B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.