

P/N NAS1189E06P3

Description

Fastener Length: 3/16", Thread: 6-32, Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1189E06P3

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-113-2867

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS1189E06P3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.038 Inches Minimum And 0.131 Inches Maximum
Fastener Length:	0.157 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.231 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Fed Spec Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E06P3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.