

**Description**

Fastener Length: 5/16", Thread: 6-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1189E06P5LK
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-505-3084
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1189E06P5LK Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.224 Inches Minimum And 0.255 Inches Maximum
<b>Fastener Length:</b>	0.281 Inches Minimum And 0.312 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.216 Inches Minimum And 0.226 Inches Maximum
<b>Locking Feature:</b>	Strip
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	Center Fuselage
<b>Nominal Thread Diameter:</b>	0.138 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Locking Feature Material:</b>	Plastic Polychlorotrifluoroethylene
<b>Special Features:</b>	Screw;self-lock;full Thread; Kel-f Strip Type Element
<b>Thread Series Designator:</b>	Unjc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E06P5LK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.