



Military-Fasteners.com

P/N NAS1189E06P5LK

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E06P5LK
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-505-3084
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189E06P5LK Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.224 Inches Minimum And 0.255 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.216 Inches Minimum And 0.226 Inches Maximum
Locking Feature:	Strip
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Center Fuselage
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Locking Feature Material:	Plastic Polychlorotrifluoroethylene
Special Features:	Screw;self-lock;full Thread; Kel-f Strip Type Element
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E06P5LK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.