

# **P/N NAS1189E06P8L**

### **Description**

Fastener Length: 1/2", Thread: 6-32, Thread Length: 1/2",

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS1189E06P8L
Minimum Qty (MOQ):	5
NSN:	5305-01-467-0920
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS1189E06P8L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.500 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1200 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

### **How to Order**

Order this socket head cap screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/socket+head+cap+screws/NAS1189E06P8L">https://military-fasteners.com/screws/socket+head+cap+screws/NAS1189E06P8L</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.