



Military-Fasteners.com

P/N NAS1189E06T5L

Description

Fastener Length: 5/16", Thread: 6-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E06T5L
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-286-3101
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093490, Bolt / Nut / Screw / Clips / Fastener / Etc



* See page 2 for technical characteristics

P/N NAS1189E06T5L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.162 Inches Minimum And 0.255 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.231 Inches Minimum And 0.279 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Offset Cruciform (torque Set)
Nominal Thread Diameter:	0.138 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Fastener
Material:	Plastic Polyamide Locking Feature
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Fastener
Surface Treatment:	Passivate Fastener
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Fastener
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E06T5L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.