

**Description**

Fastener Length: 3/8", Thread: 8-32, Thread Length: 19/64"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1189E08P6H                             |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5305-01-050-6478                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS1189E08P6H Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.214 Inches Minimum And 0.307 Inches Maximum                      |
| <b>Fastener Length:</b>                               | 0.344 Inches Minimum And 0.375 Inches Maximum                      |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.270 Inches Minimum And 0.332 Inches Maximum                      |
| <b>Locking Feature:</b>                               | Patch Threads  |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                      |
| <b>Countersink Angle:</b>                             | 100.0 Degrees Nominal  |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                           |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                               |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1189 Professional/Industrial Association Standard         |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E08P6H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.