



Military-Fasteners.com

P/N NAS1189E08T8K

Description

Fastener Length: 1/2", Thread: 8-32, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS1189E08T8K                             |
| Minimum Qty (MOQ):      | 15 EA                                     |
| NSN:                    | 5305-01-088-9542                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N NAS1189E08T8K Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.339 Inches Minimum And 0.432 Inches Maximum              |
| <b>Fastener Length:</b>                               | 0.469 Inches Minimum And 0.500 Inches Maximum              |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.270 Inches Minimum And 0.332 Inches Maximum              |
| <b>Locking Feature:</b>                               | Pellet Threads Or Strip Threads                            |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                              |
| <b>Nominal Thread Diameter:</b>                       | 0.164 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum             |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                   |
| <b>Material:</b>                                      | Iron Alloy 660 Fastener                                    |
| <b>Material:</b>                                      | Plastic Locking Feature                                    |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Fastener        |
| <b>Surface Treatment:</b>                             | Passivate Fastener   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Fastener        |
| <b>Thread Series Designator:</b>                      | Unjc   |
| <b>Specification/standard Data:</b>                   | 80205-nas1189 Professional/industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E08T8K> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.