

## **P/N NAS1189E3P10LH**

### **Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge

# Order this part online

#### **Additional Information**

SKU / Model: NAS1189E3P10LH

Minimum Qty (MOQ): 10

NSN: 5305-01-551-9208

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



<sup>\*</sup> See page 2 for technical characteristics

## P/N NAS1189E3P10LH Specifications

Thread Direction:	Right-hand
Fastener Length:	0.625 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.371 Inches Minimum And 0.385 Inches Maximum
Locking Feature:	Strip Locking Feature
Internal Drive Style:	Cross Recess Type 1
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Special Features:	Screw Is 0.1900-32 Unjf 3a
Material:	Plastic Nylon Locking Feature
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall

## **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P10LH">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P10LH</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P10LH">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P10LH</a> and selecting the