

**Description**

Fastener Length: 5/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS1189E3P10LH
Minimum Qty (MOQ):	10
NSN:	5305-01-551-9208
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS1189E3P10LH Specifications

<b>Thread Direction:</b>	Right-hand
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.371 Inches Minimum And 0.385 Inches Maximum
<b>Locking Feature:</b>	Strip Locking Feature
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Countersink Angle:</b>	100.0 Degrees Nominal
<b>Special Features:</b>	Screw Is 0.1900-32 Unjf 3a
<b>Material:</b>	Plastic Nylon Locking Feature
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall

## How to Order

Order this close tolerance bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P10LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.