

Description

Fastener Length: 3/4", Thread: 10-32, Thread Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E3P12B
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-385-3822
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE
AVAILABLE

P/N NAS1189E3P12B Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.577 Inches Minimum And 0.670 Inches Maximum
Fastener Length:	0.719 Inches Minimum And 0.750 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Locking Feature:	Strip
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Locking Feature Material:	Plastic Polyamide
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P12B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.