



Military-Fasteners.com

P/N NAS1189E3P14N

Description

Fastener Length: 7/8", Thread: 10-32, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E3P14N
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-147-4750
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189E3P14N Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.702 Inches Minimum And 0.795 Inches Maximum
Fastener Length:	0.844 Inches Minimum And 0.875 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.371 Inches Minimum And 0.385 Inches Maximum
Locking Feature:	Pellet Threads
Internal Drive Style:	Cross Recess Type II
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P14N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.