

P/N NAS1189E3P5

Description

length: 5/16", thread: 10-32, flat head, self locking, full thread, corrosion resistant steel, NAS1189 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS1189E3P5

Minimum Qty (MOQ): 25

NSN: 5305-01-309-6309

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS1189E3P5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.232 Inches Nominal
Fastener Length:	0.312 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS1189E3P5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.