

## **P/N NAS1189E3P8H**

## **Description**

Fastener Length: 1/2", Thread: 10-32, Thread Length: 13/32",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS1189E3P8H

Minimum Qty (MOQ): 25

NSN: 5305-01-104-5879

Schedule B: 7318.15.2091

ECCN: EAR99









# P/N NAS1189E3P8H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Nominal
Fastener Length:	0.500 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.371 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty li Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this close tolerance bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P8H">https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E3P8H</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.