

Description

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189E4T9L
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-209-7896
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS1189E4T9L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.381 Inches Nominal
Fastener Length:	0.558 Inches Minimum And 0.589 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.491 Inches Minimum And 0.507 Inches Maximum
Locking Feature:	Strip
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	180000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Iron Alloy 660
Locking Feature Material:	Plastic Polychlorotrifluoroethylene
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Surface Finish:	32.0 Microinches
Special Features:	32.0 Microinche Finish Underside Of Head
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E4T9L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.