

Description

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1189E4T9L |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-209-7896 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1189E4T9L Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.381 Inches Nominal |
| Fastener Length: | 0.558 Inches Minimum And 0.589 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.491 Inches Minimum And 0.507 Inches Maximum |
| Locking Feature: | Strip |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 180000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Iron Alloy 660 |
| Locking Feature Material: | Plastic Polychlorotrifluoroethylene |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Surface Finish: | 32.0 Microinches |
| Special Features: | 32.0 Microinche Finish Underside Of Head |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E4T9L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.