

**Description**

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS1189E4T9L
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-209-7896
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS1189E4T9L Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.381 Inches Nominal
<b>Fastener Length:</b>	0.558 Inches Minimum And 0.589 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.491 Inches Minimum And 0.507 Inches Maximum
<b>Locking Feature:</b>	Strip
<b>Internal Drive Style:</b>	Torque Set
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Iron Alloy 660
<b>Locking Feature Material:</b>	Plastic Polychlorotrifluoroethylene
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Surface Finish:</b>	32.0 Microinches
<b>Special Features:</b>	32.0 Microinche Finish Underside Of Head
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E4T9L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.