

**Description**

Fastener Length: 57/64", Thread: 1/4-28, Thread Length: 57/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS1189E4T9LH    |
| Minimum Qty (MOQ): | 10 EA            |
| NSN:               | 5305-01-522-7550 |
| Schedule B:        | 7318.15.6080     |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N NAS1189E4T9LH Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.863 Inches Minimum And 0.894 Inches Maximum              |
| <b>Fastener Length:</b>                               | 0.863 Inches Minimum And 0.894 Inches Maximum              |
| <b>Head Style:</b>                                    | Flat Countersunk   |
| <b>Head Diameter:</b>                                 | 0.442 Inches Minimum And 0.507 Inches Maximum              |
| <b>Locking Feature:</b>                               | Patch Threads Or Pellet Threads Or Strip Threads           |
| <b>Internal Drive Style:</b>                          | Offset Cruciform (torque Set)                              |
| <b>End Item Identification:</b>                       | Ch-53g Helicopter  |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                              |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum             |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                   |
| <b>Part Name Assigned By Controlling Agency:</b>      | Screw, Self-locking, Flat 100 Degree Head, Full Thread     |
| <b>Material:</b>                                      | Steel Corrosion Resisting Overall                          |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall         |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall         |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas1189 Professional/Industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189E4T9LH> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.