

Description

Fastener Length: 5/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS1189V3T5L |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-434-0876 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS1189V3T5L Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.250 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.125 Inches Minimum And 0.176 Inches Maximum |
| Locking Feature: | Strip |
| Internal Drive Style: | Torque Set |
| Nominal Thread Diameter: | 0.190 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Screw Material: | Titanium Alloy Uns R56400 |
| Locking Feature Material: | Plastic Polyamide |
| Screw Material Document And Classification: | Ams 4928 Assn Std Single Material Response And Ams 4967 Assn Std Single Material Response |
| Locking Feature Material Document And Classification: | Mil-f-18240 Mil Spec Single Material Response |
| Bearing Surface Of Head Surface Finish: | 32.0 Microinches |
| Shank Surface Finish: | 32.0 Microinches |
| Thread Surface Finish: | 32.0 Microinches |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189V3T5L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.