



Military-Fasteners.com

P/N NAS1189V3T5L

Description

Fastener Length: 5/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189V3T5L
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-434-0876
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189V3T5L Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.125 Inches Minimum And 0.176 Inches Maximum
Locking Feature:	Strip
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy Uns R56400
Locking Feature Material:	Plastic Polyamide
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response And Ams 4967 Assn Std Single Material Response
Locking Feature Material Document And Classification:	Mil-f-18240 Mil Spec Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189V3T5L> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.