



Military-Fasteners.com

P/N NAS1189V3T6LK

Description

Fastener Length: 3/8", Thread: 10-32, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS1189V3T6LK
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-442-6183
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS1189V3T6LK Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.313 Inches Maximum
Fastener Length:	0.313 Inches Minimum And 0.375 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.322 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Torque Set
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Titanium Alloy Uns R56400
Locking Feature Material:	Plastic Polychlorotrifluoroethylene
Screw Material Document And Classification:	Ams 4928 Assn Std Single Material Response Or Ams4967 Assn Std Single Material Response
Locking Feature Material Document And Classification:	Ams 3650 Assn Std Single Material Response
Bearing Surface Of Head Surface Finish:	32.0 Microinches
Shank Surface Finish:	32.0 Microinches
Thread Surface Finish:	32.0 Microinches
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas1189 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/NAS1189V3T6LK> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.